



DESVOYS

KEY POINTS

- Very sturdy housing structure with 3 thick beams
- 4-row rotor equipped with Y cutters
- Power transmission via oversize gearbox, shaft and trumpets
- Reversible Y cutters mounted onto treated bushes
- Optional: rear roller with mud scraper; heavy duty type pallet cutters

SPECIFICATIONS

WORKING WIDTH	SINGLE DRIVE Fixed or offset model (except 2.40m)						DOUBLE DRIVE fixed or offset model	
	2.40		2.80		3.20		2.80	3.20
PTO speed (rpm)	540	1000	540	1000	540	1000	1000	
Number of belts	4		5		5		2 x 3	
Tractor power rating (depending on PTO) (hp)	70-200			90-200				
Coupling	For welded fixed coupling						For fixed coupling, Centred, bolted on	
Coupling category	Cat. 2 clevis hitch							
Number of cutters (in Y)	56		64		76		64	76
Counter-cutter	Upper and lower, U-shaped, removable							
Adjustable terrain tracking	Pair of semi-pivoting wheels - Pair of bolt-on skids in HARDOX <small>ARCELORMITTAL</small>							
Rear cover	Mobile cover							
Housing thickness (mm)	4							
Armour plate (mm)	As standard on the housing - Bolt-on - Thickness 4							
Weight *(kg)	1220		1400		1504		1610	1730

*Add 160 kg for offset models

OPTIONS

Several cutter assemblies
Front chain curtains
Rear wheel with assisted adjustment

Hardox armour plates
Induction time meter
Signalling kit