



KEY POINTS

- Oversize chassis composed of bushed pivots
- Patented protection for side transmission systems
- 1 Pair of semi-pivoting twin wheels with damper and 1 pair of single wheels
- Hydraulic folding shredder
- Rotor equipped with Y cutters + fan
- Front element can be used solo, in push or pull mode

SPECIFICATIONS

WORKING WIDTH (M)	8.40 (Rear element)	3.20 (Front element)
PTO speed (rpm)	1000	
Number of belts	2 x 5	2 x 3
Gearbox power with built-in free wheel (hp)	410	220
Tractor power rating (hp)	200-400	90-220
Coupling	Fixed	Fixed
Coupling category	Cat. 3 clevis hitch	Cat. 2 clevis hitch
Number of cutters	104 Y + 52 fans	76 Y cutters
Counter-cutter	Upper and lower smooth, removable	Upper and lower removable combs
Adjustable terrain tracking	1 Pair of semi-pivoting twin wheels with damper and 1 pair of single wheels. Pair of bolt-on skids in HARDOX	Ø 245 roller Pair of bolt-on skids in HARDOX
Rear covers	Mobile covers	Closed housing
Housing thickness (mm)	4	
Armour plate (mm)	As standard on the housing - Bolt-on - Thickness 4	As standard on the housing - Welded - Thickness 4
Weight (kg)	4300	1790

OPTIONS

Pallet cutter configuration Y cutters + fan Upper and lower comb counter-cutters	Roller with mud scraper Hardox armour plates Time and surface area meter
--	--