

STANDARD SINGLE-DISC



KEY POINTS

- Automatic retraction system for the cutter unit
- The pressure can be adjusted by a manual pump to bypass obstacles
- 3-position reversible cutters
- Large diameter thrust disc (700 mm)
- Rotor with 3 removable cutters on treated bushes and shredder body fitted with 5 counter-cutters

SPECIFICATIONS

POSITION OF SHREDDER	3-point rear	3-point front	loader	3-point front	telescopic
Shredding side	Shredding on right			Shredding on left	
Working width (mm)	1000				
Coupling	Cat. 1 and 2		Adaptation (optional)	Cat. 1 and 2	Adaptation (optional)
Offset values	Hydraulic 620 mm				
Tilt	Hydraulic tilting - +90°/-15° - Motor 26 cc				
Work rate req'd (L/min)	40 to 50				
Rotor	3 removable cutters				
Cutting height (mm)	65				
Terrain tracking	Thrust disc free to rotate with spring-loaded HARDOX wear-resistant base plate				
Weight (kg)	370		360	370	360
Basic hydraulic equipment	1 selector (for offset and tilt) + control handle				
Equipment required	1 D.A. to drive selector - 12 volt supply - 1 S.A. With direct return to power motor				

OPTIONS

Central hydraulic unit	Sensor
Solenoid valve control kit	Cooler