



KEY POINTS

- High rotation speed rotor equipped with B7 hammer cutters.
- Wide front opening
- Profiled housing with truncated corners, protective cover and rounded bolts
- Clevis hitch with hydraulic offset on 2 slides
- Height-adjustable roller
- Inner skids (10 mm) with bolt-on **HARDOX** WEAR PLATE wear base plate

SPECIFICATIONS

| WORKING WIDTH | 1.30 | | 1.45 | | 1.60 | | 1.75 | | 1.95 | |
|-------------------------------|------------------------------|------|------|------|------|------|------|------|------|------|
| PTO speed (rpm) | 540 | 1000 | 540 | 1000 | 540 | 1000 | 540 | 1000 | 540 | 1000 |
| Number of belts | 3 | | | | 4 | | | | | |
| Tractor power rating (hp) | 40-110 | | | | | | | | | |
| Cat. 1 & 2 coupling | Clevis hitch - Can be offset | | | | | | | | | |
| Number of hammer cutters (B7) | 10 | | 12 | | | | 14 | | 16 | |
| Weight (kg) | 610 | | 640 | | 670 | | 690 | | 740 | |

OPTIONS

| | |
|------------------------------------|-------------------------|
| Front anti-ejection chain curtains | Additional transmission |
| Bolt-on armour plate | Roller mud scraper |
| Retention kit | Induction time meter |